

WARNING LIGHT LO



Compliance with:

PN-EN 12352

L6/L7

- P1; C1; R0; A1; I0; F3; O1; M3; T1; S0

Characteristic:

Warning light LO type is a road work warning light, dedicate to work on roads as a warning element during the danger. This product is increasing safety level on our roads. Using high LED technology makes low power consumption and longer life of light source.

Technical data:

Light source:	LED
Light source life:	≥ 10 lat
Luminous intensity:	26 cd ± 5%
Light signal emitting area:	254 cm ²
Impulse frequency:	60±3 / min.
Automatic night operation @:	> 260 lux
Operating time (in hour):	
For LO – 01x12	
- 1 battery 6V 4R25 45 Ah	1500 h (@ +25 °C)
LO – 02x12	
- 2 batteries 6V 4R25 45 Ah	3000 h (@ +25 °C)
Overall dimensions:	
height:	360 mm (380 mm LO – 02)
width:	180 mm
thickness:	105 mm (95 mm LO – 02)
Weight:	1,3 kg (1 battery)
	1,7 kg (2 batteries)

Types

LO-0111x	warning light with 1 battery, yellow double side, compliance with L6 class
LO-0112x	warning light with 1 battery, yellow single side, compliance with L7 class
LO-0121x	warning light with 1 battery, red double side, compliance with L6 class
LO-0122x	warning light with 1 battery, red single side, compliance with L7 class
LO-0211x	warning light with 2 batteries, yellow double side, compliance with L6 class
LO-0212x	warning light with 2 batteries, yellow single side, compliance with L7 class
LO-0221x	warning light with 2 batteries red double side, compliance with L6 class
LO-0222x	warning light with 2 batteries, red single side, compliance with L7 class

x – is a power supply type

1- battery 6V 4R25 25 Ah

2- battery 6V 4R25 45 Ah

3- battery Pb 6V 4R25 5 Ah rechargeable

4- without battery